



MB200EE

Product		Control Unit	
Model		Emergency	
Type		Turn to Release with Label	
Contact		1NC	
Color		Red	
Dia		22 mm	
Head Dia		40 mm	
Current	Ie	3 A (240V AC)	
Usage Category		AC 15	
Mechanical Life	Min Qty	300000	
Electrical Life	Min Qty	100000	
Operating Frequency	On-Off/Hour	Mech. 3000 Elec. 1200	
Insulation Voltage	Ui	250V	
Impulse Withstand Voltage	Uimp	2.5 kV	
Dielectric Strength (Body-Contact)		2.500V AC	
Dielectric Strength (Contact-Contact)		1.500V AC	
Isolation Resistance		10 MΩ Min. (500 V DC)	
Operating Temperature		-15 / + 80 °C	
Pollution Degree		3	
Protection Degree		IP50	
Contact Material		AgNi	
Cable Section		1.5-2.5 mm ²	
Screw Torque		1,5 Nm	
Short Circuit Breaking Capacity	Ics	1 kA	
Serial		MB Series Plastic	
Specifications		Non-flammable V0 PA6.6 contact blocks	
		Monoblock strong body	
		Finger safe protection	

Standards / Certificates IEC 60947-5-1 TS EN 60947-5-1

