


### MB202DK

Product		Control Unit	
Model		Spring	
Type		Flush	
Contact		2NC	
Color		Red	
Dia		22 mm	
Current	<b>Ie</b>	3 A (240V AC)	
Usage Category		AC 15	
Mechanical Life	<b>Min Qty</b>	300000	
Electrical Life	<b>Min Qty</b>	100000	
Operating Frequency	<b>On-Off/Hour</b>	Mech. 3000 Elec. 1200	
Insulation Voltage	<b>Ui</b>	250V	
Impulse Withstand Voltage	<b>Uimp</b>	2.5 kV	
Dielectric Strength (Body-Contact)		2.500V AC	
Dielectric Strength (Contact-Contact)		1.500V AC	
Isolation Resistance		10 MΩ Min. (500 V DC)	
Operating Temperature		-15 / + 80 °C	
Pollution Degree		3	
Protection Degree		IP50	
Contact Material		AgNi	
Cable Section		1.5-2.5 mm <sup>2</sup>	
Screw Torque		1,5 Nm	
Short Circuit Breaking Capacity	<b>Ics</b>	1 kA	
Serial		MB Series Plastic	
Specifications		Non-flammable V0 PA6.6 contact blocks	
		Monoblock strong body	
		Finger safe protection	
Standards / Certificates		IEC 60947-5-1 TS EN 60947-5-1	

CE

ERT



TSE