



<b>PA1191</b>		
Hole Qty		1 Hole
Ingredients		BPR10K
Product		PA Series 1 Hole BPR10K Yellow-Black Lift Station
Color		Yellow-Black
Current	<b>Ie</b>	4A (250V AC)
Usage Category		AC15
Mechanical Life	<b>Min Qty</b>	1000000
Electrical Life	<b>Min Qty</b>	100000
Operating Frequency	<b>On-Off/Hour</b>	Mech. 3000 Elec. 1200
Insulation Voltage	<b>Ui</b>	300 V
Impulse Withstand Voltage	<b>Uimp</b>	2.5 kV
Dielectric Strength (Body-Contact)		2.500V AC
Dielectric Strength (Contact-Contact)		1.500V AC
Isolation Resistance		10 MΩ (500 V DC)
Operating Temperature		-15 / + 80 °C
Pollution Degree		3
Protection Degree		IP65
Contact Material		AgNi
Cable Section		1.5-2.5 mm <sup>2</sup>
Screw Torque		1.5Nm
Short Circuit Breaking Capacity	<b>Ics</b>	1kA
Serial		PA Series
Specifications		Suitable for Ø22 mm control units Aesthetic, durable and ergonomic design
Standards / Certificates		TS EN 60947-5-1 UL 508 VDE 0660

