



### PSA032CD334S

Product	Cam Switch	(R)
Label/Position	(1-0-2)	
Switch Type	Motor Control Double Cycle	
Pole / Phase	3 Phase	
Frame Size	64*64	
Current	<b>Ie</b> 32A	
Usage Category	AC21A	
Mechanical Life	<b>Min Qty</b> 100000	
Electrical Life	<b>Min Qty</b> 50000	
Operating Frequency	<b>On-Off/Hour</b> Mech.120 Elec.120	
Insulation Voltage	<b>Ui</b> 690V	
Impulse Withstand Voltage	<b>Uimp</b> 4 kV	
Dielectric Strength (Body-Contact)	1.890V AC	
Dielectric Strength (Contact-Contact)	1.890V AC	
Isolation Resistance	10 MΩ MIN. (500 V DC)	
Operating Temperature	-25 / +80 °C	
Pollution Degree	3	
Protection Degree	IP54	
Contact Material	AgNi	
Cable Section	4 mm <sup>2</sup>	
Spin Angle	60°	
Short Circuit Breaking Capacity	<b>Ics</b> 6 kA	
Serial	PSA Series	
Specifications	High precision	
	Variety of products for wide application fields	
	Long life time	
	Compact design	
Standards / Certificates	TS EN 60947-3	

CE

ERT



TSE