

PRODUCT-DETAILS

S282 UC FS K20

Miniature Circuit Breaker - S280 UC FS - 2P - K - 20 ampere



General Information

Extended Product Type	S282 UC FS K20
Product ID	11865416
EAN	8012542337935
Catalog Description	Miniature Circuit Breaker - S280 UC FS - 2P - K - 20 ampere
Long Description	S282 UC FS K20 Miniature Circuit Breaker

Technical

Number of Poles	2
Number of Protected Poles	2
Tripping Characteristic	K
Rated Current (I_n)	20 A
Rated Insulation Voltage (U_i)	500 V
Rated Short-Circuit Capacity (I_{cn})	(230 V) 10 kA (400 V) 25 kA
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	3
Rated Impulse Withstand Voltage (U_{imp})	4 kV
Degree of Protection	IP20
Connecting Capacity	Rigid 0 ... 25 mm ²

Flexible 0 ... 25 mm²

Built-In Depth (t ₂)	68 mm
----------------------------------	-------

Environmental

Ambient Air Temperature	Operation -25...55 °C
-------------------------	-----------------------

Dimensions

Product Net Width	0.035 m
Product Net Depth / Length	0.058 m
Product Net Height	0.090 m
Product Net Weight	0.281 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.036 m
Package Level 1 Depth / Length	0.096 m
Package Level 1 Height	0.085 m
Package Level 1 Gross Weight	0.290 kg
Package Level 1 EAN	8012542337935

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362010

Certificates and Declarations (Document Number)

Instructions and Manuals	Not requested
--------------------------	---------------

Popular Downloads

Data Sheet, Technical Information	2CSC401002B0901
Instructions and Manuals	Not requested

Classifications

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

