

PRODUCT-DETAILS

# CL2-515Y

## Compact Pilot Light Yellow LED 110-130V DC



### General Information

Extended Product Type	CL2-515Y
Product ID	1SFA619403R5153
EAN	7320500556306
Catalog Description	Compact Pilot Light Yellow LED 110-130V DC
Long Description	Compact Pilot Light - Pilot light head - Yellow - Illuminated - Lamptype: LED 110-130V DC

### Ordering

E-Number (Finland)	2313539
E-Number (Norway)	4373527
E-Number (Sweden)	3705768
EAN	7320500556306
Minimum Order Quantity	10 piece
Customs Tariff Number	8536619090

### Dimensions

Product Net Width	0.03 m
Product Net Height	0.03 m
Product Net Depth / Length	0.052 m
Product Net Weight	0.1 kg

---

**Container Information**


---

Package Level 1 Units	bag 10 piece
Package Level 1 EAN	7320500475607

---



---

**Environmental**


---

RoHS Status	Following EU Directive 2015/863 July 22, 2019 (RoHS 3)
-------------	--

---



---

**Additional Information**


---

Actuator Type	Pilot light head
Color	Yellow
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20
Illumination	Illuminated
Lamp Type	110-130 V DC, integrated LED
Product Main Type	CL2
Product Name	Pilot Light
Product Range	Compact
Rated Operational Voltage	110 ... 130 V DC

---



---

**Certificates and Declarations (Document Number)**


---

CCC Certificate	2003010305054693_
CQC Certificate	CQC2003010305054693
cURus Certificate	UL_E496500-20171020
Data Sheet, Technical Information	1SFC151007C02__
Declaration of Conformity - CCC (CCC)	2020980305001187
Declaration of Conformity - CE	2CMT2015-005451
DNV GL Certificate	9AKK107046A3749
Environmental Information	1SFC151009D0201
Instructions and Manuals	1SFC151011M0201
RoHS Information	2CMT2015-005451

---



---

**Classifications**


---

ETIM 5	EC000272 - Indicator light complete
ETIM 6	EC000272 - Indicator light complete
ETIM 7	EC000272 - Indicator light complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

---

## Categories

---

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range

