

PRODUCT-DETAILS

SC-JB8-2

SC-JB8-2 Short circuit bridges - Yellow



| General Information | |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | SC-JB8-2 |
| Product ID | 1SNK900652R0000 |
| EAN | 3472599872967 |
| Catalog Description | SC-JB8-2 Short circuit bridges - Yellow |
| Long Description | Allow safe short-circuiting of Current Tranformers circuits, - Insulated, - Fully operated by screwdriver, - Short circuited fixed position secured thanks to AJS9 tightening, - Adapted hook shape maintains the bridge on the terminal block in the non short-circuited position, - The orange version can be used as fixed jumpers. |

| Ordering | |
|------------------------|----------|
| Color | Yellow |
| Minimum Order Quantity | 25 piece |
| Customs Tariff Number | 85389099 |

| Popular Downloads | |
|-------------------|-----------------|
| Instructions and | 1SNK160027C0201 |
| Manuals | |

Dimensions

Product Net Width 8 mn

Object Classification

Code

Χ

| Product Net Height | 24.6 mm |
|-------------------------------|---------|
| Product Net Depth / Length | 13.9 mm |
| Product Net Weight | 2 g |

| Technical | |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Spacing | 8 mm |
| Function | Short Circuit Bridges |
| Rated Current (In) | Main Circuit 5 A |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Insulation Material | Polyamide |
| Mounting on DIN Rail | G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715 |
| Recommended Screw Driver | 3.5 mm |
| Suitable For | D6/8.ST.RS ZS10-PE-R1 ZS10-R1 ZS10-ST ZS10-ST-T4 |

| Technical UL/CSA | |
|------------------------|-----|
| Flammability According | V-0 |
| to UL94 | |

| Environmental | |
|---------------|-----------------------------------------------------------------|
| Ambient Air | Operation -55 +110 °C |
| Temperature | Storage -55 +110 °C |
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

| 1SNK160027C0201 |
|-----------------|
| 1SND230528F0200 |
| |
| _ |

| Container Information | |
|-----------------------------------|---------------|
| Package Level 1 Units | 25 piece |
| Package Level 1 Width | 125 mm |
| Package Level 1 Depth / Length | 170 mm |
| Package Level 1 Height | 20 mm |
| Package Level 1 Gross Weight | 0.05 kg |
| Package Level 1 EAN | 3472599872967 |
| Package Level 2 Units | 500 piece |

SC-JB8-2 3

| Package Level 2 Width | 175 mm |
|---------------------------------|-------------|
| Package Level 2 Depth / Length | 227 mm |
| Package Level 2 Height | 130 mm |
| Package Level 2 Gross Weight | 1 kg |
| Package Level 3 Units | 24000 piece |

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Connection\ Devices \rightarrow Terminal\ Blocks\ Accessories \rightarrow Short\ Circuit\ Bridges$

