

PRODUCT-DETAILS

# 3125P6W

## Ind. P&S#3125P6W



### General Information

Extended Product Type	3125P6W
Product ID	2CMA166816R1000
EAN	7392696668163
Catalog Description	Ind. P&S#3125P6W
Long Description	Plug, earthing sleeve position 6h, rated current 125A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red

### Ordering

E-Number (Sweden)	E2416305
E-Number (Finland)	2421650
E-Number (Norway)	1563913
EAN	7392696668163
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

### Dimensions

Product Net Width	127 mm
Product Net Height	127 mm

Product Net Weight	1.43 kg
Mechanical Drawings	9AKK107492A4190

---

## Container Information

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	1.54 kg
Package Level 1 EAN	7392696668163
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	121.64 kg
Package Level 2 EAN	7392696070287
Package Level 2 Units	pallet (lift) 66 piece

---

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

---

## Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 50 mm <sup>2</sup>
Cable Diameter	24 ... 48 mm
Cable Entry Position	Cable entry, compression gland, internal and external cable clamp
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#3125P6W
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TP
Product Name	Industrial Plug
Protection Type	Watertight
Rated Current ( $I_n$ )	125 A
Rated Voltage ( $U_r$ )	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Plugs
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7001 - Silver Grey

## Classifications

eClass	27440509
UNSPSC	39120000

## Technical

Wire Size	3 ... 1 AWG
Tightening Torque	WireClamp5.6 N·m

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Plugs

