

PRODUCT-DETAILS

CAF6-11K

CAF6-11K Auxiliary Contact



General Information

Extended Product Type	CAF6-11K
Product ID	GJL1201330R0001
EAN	4013614142642
Catalog Description	CAF6-11K Auxiliary Contact
Long Description	The CAF6-11K is an auxiliary contact for front mounting with 2 auxiliary contact and screw terminals.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Popular Downloads

Data Sheet, Technical Information	1SBC100173C0201
Instructions and Manuals	2CDC102005M0101
Instructions and Manuals (Part 2)	2CDC102005M0101
Dimension Diagram	GJL1200446F0001

Dimensions

Product Net Width	47.5 mm
Product Net Height	29 mm
Product Net Depth / Length	26.5 mm
Product Net Weight	0.02 kg

Technical

Rated Operational Voltage	Auxiliary Circuit 690 V AC Auxiliary Circuit 250 V DC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U _{imp})	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i)	690 V
Degree of Protection	IP20
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ²
Tightening Torque	Auxiliary Circuit 0.8 ... 1.1 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Main Contacts NC	0
Number of Main Contacts NO	0
Conventional Free-air Thermal Current (I _{th})	Auxiliary Circuit 6 A
Product Name	Auxiliary Contact
Suitable For	K6 KC6
Suitable for Product Class	Mini Contactors

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 600 V AC/DC
Connecting Capacity Auxiliary Circuit UL/CSA	Stranded 1/2x 22-10 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 7 in·lb
Contact Rating UL/CSA	A600

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc.	11 ms Pulse 15g

to IEC 60068-2-27

Resistance to Vibrations acc. to IEC 60068-2-6	5g / 5 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CCC Certificate	1SAA938000-3804
cULus Certificate	cUL_E48139
Declaration of Conformity - CE	1SAD938516-0001
EAC Certificate	1SAA938002-2701
GL Certificate	1SAA938000-0403
Instructions and Manuals	2CDC102005M0101
Instructions and Manuals (Part 2)	2CDC102005M0101
RMRS Certificate	1SAA938001-0703
RoHS Information	1SAD938514-0001
UL Certificate	UL_E48139

Container Information

Package Level 1 Width	115 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	54 mm
Package Level 1 Gross Weight	0.24 kg
Package Level 1 EAN	4013614412226
Package Level 1 Units	10 piece

Classifications

Object Classification Code	K
ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	7.0 27371302
UNSPSC	39121522
E-Number (Sweden)	3210092

Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors Accessories

