

PRODUCT-DETAILS

NF22E-14

NF22E-14 250-500V50/60HZ-DC Contactor Relay



Información General

Tipo de producto extendido	NF22E-14
Código de producto	1SBH137001R1422
EAN	3471523100145
Descripción corta	NF22E-14 250-500V50/60HZ-DC Contactor Relay

Descripción larga	<p>NF contactor relays are used for switching auxiliary and control circuits. NF contactor relays include an electronic coil interface accepting a wide control voltage U_c min. ... U_c max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. NF contactor relays can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. NF contactor relays have built-in surge protection and do not require additional surge suppressors. - Poles: 4-pole contactor relays (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1 and including the "Mechanically Linked" symbol on the contactor relay side) - Control Circuit: AC or DC operated - Accessories: a wide range of Accessories is available.</p>
-------------------	--

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85364900

Descargas Populares

Instrucciones y manuales	1SBC101027M6801
--------------------------	-----------------

Dimensiones

Ancho del product	45 mm
Largo del product	77 mm
Alto del producto	86 mm
Peso del product	0.31 kg

Technical

Number of Auxiliary Contacts NO	2
Number of Auxiliary Contacts NC	2
Standards	IEC 60947-5-1 and EN 60947-5-1, UL 508, CSA C22.2 N°14
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-5-1, q = 40 °C 16 A
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Short-time Withstand Current (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Maximum Electrical Switching Frequency	(AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour
Rated Operational Current DC-13 (I _e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Maximum Mechanical Switching Frequency	6000 cycles per hour
Rated Control Circuit Voltage (U _c)	50 Hz 250 ... 500 V 50 Hz / 60 Hz 250 ... 500 V 60 Hz 250 ... 500 V DC Operation 250 ... 500 V
Operate Time	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
Wire Stripping Length	Auxiliary Circuit 10 mm Control Circuit 10 mm
Grado de protección	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20

Terminal Type	Screw Terminals
---------------	-----------------

Technical UL/CSA

Tightening Torque UL/CSA	Auxiliary Circuit 11 IA Control Circuit 11 IA
-----------------------------	--

Ambiente

Temperatura ambiente	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... +70 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible	3000 m
Resistance to Vibrations acc. to IEC 60068-2-6	5 ... 300 Hz 4 g closed position / 2 g open position
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 25 K40 Open, Shock Direction: B1 5 K40 Shock Direction: A 30 K40 Shock Direction: B2 15 K40 Shock Direction: C1 25 K40 Shock Direction: C2 25 K40
RoHS Status	Following EU Directive 2011/65/EU

Certificados y Declaraciones (Número de Documento)

ABS Certificate	ABS_15-GE1349500-PDA_90682247
BV Certificate	BV_2634H24899B0
CB Certificate	CB_SE-93051M2
CCC Certificate	2020980303000185
CQC Certificate	CQC2019010303267993
cUL Certificate	UL_20180227_E252354_2_1
Declaration of Conformity - CCC	CQC2011010303465426
Declaración de conformidad - CE	1SBD250005U1000
DNV Certificate	DNV-GL_TAE00001BV-3
DNV GL Certificate	DNV-GL_TAE00001BV-3
EAC Certificate	EAC_RU C-FR ME77 B03544
Environmental Information	1SBD250151E1000
GL Certificate	DNV-GL_TAE00001BV-3
GOST Certificate	GOST_POCCFR.ME77.B06804.pdf
Instrucciones y manuales	1SBC101027M6801
LR Certificate	LRS_C1400038
RINA Certificate	RINA_ELE240318XG
RMRS Certificate	RMRS_1802702280
RoHS Information	1SBD250005U1000
UL Certificate	UL_20130206-E252354-2-1
UL Listing Card	UL_E252354

Información de Embalaje

Embalaje Nivel 1 Unidades	box 1 piece
Embalaje Nivel 1 Ancho	87 mm
Embalaje Nivel 1 Largo	79 mm

Embalaje Nivel 1 Alto	47 mm
Embalaje Nivel 1 Peso	0.31 kg
Embalaje Nivel 1 EAN	3471523100145
Package Level 2 Units	box 27 piece
Package Level 2 Width	250 mm
Package Level 2 Depth / Length	300 mm
Package Level 2 Height	315 mm
Package Level 2 Gross Weight	16.74 kg
Package Level 3 Units	1296 piece

Clasificaciones

Object Classification Code	K
ETIM 4	EC000196 - Contactor relay
ETIM 5	EC000196 - Contactor relay
ETIM 6	EC000196 - Contactor relay
ETIM 7	EC000196 - Contactor relay
eClass	V11.0 : 27371003
UNSPSC	39121500
E-Number (Finland)	3706402
E-Number (Sweden)	3211449

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Contactores

