

PRODUCT-DETAILS

CA4-31M

CA4-31M Auxiliary Contact Block



Información General

Tipo de producto extendido	CA4-31M
Código de producto	1ISBN010140R1131
EAN	3471523130173
Descripción corta	CA4-31M Auxiliary Contact Block

Descripción larga	<p>The auxiliary contact blocks are used for the operation of auxiliary circuits and control circuits for standard industrial environments.</p> <p>Types of auxiliary contact blocks for front mounting:</p> <ul style="list-style-type: none"> • CA4 1 or 4-pole block, with instantaneous N.O., N.C. contacts • CC4 1-pole block, with N.O. leading contact or N.C. lagging contact • CAT4 2-pole block, with instantaneous N.O. + N.C. contacts and A1 / A2 coil terminal connection on front face. <p>Select the 4-pole auxiliary contact blocks CA4-..E, CA4-..M, CA4-..U or CA4-..N type, according to the contactor or contactor relay type for compliance with the standard requirements (see "Terminal marking and positioning").</p> <p>Types of auxiliary contact blocks for side mounting:</p> <ul style="list-style-type: none"> • CAL4 2-pole block, with instantaneous N.O. + N.C. contacts. <p>For clipping onto the right- and/or left-hand side of the contactors. The auxiliary contact blocks are equipped with screw type connecting terminals delivered open, protected against accidental direct contact and bear the corresponding function marking.</p>
-------------------	--

Technical

Product Name	Auxiliary Contact Block
Suitable For	AF09 AF12

AF16

Rated Operational Voltage	Auxiliary Circuit 24 ... 690 V
Rated Insulation Voltage (U_i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Operational Current AC-15 (I_{θ})	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Short-time Withstand Current (I_{ow})	for 0.1 s 140 A for 1 s 100 A
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	3
Low Coil Consumption	No
Tightening Torque	Auxiliary Circuit 1.2 N·m
Mounted Auxiliary Contacts	3 NO, 1 NC
Mounting Type	Front mounting
Wire Stripping Length	Auxiliary Circuit 10 mm
Terminal Type	Screw Terminals

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SBD250143E1000

Technical UL/CSA

Tightening Torque UL/CSA	Auxiliary Circuit 11 IA
-----------------------------	-------------------------

Dimensiones

Ancho del product	43 mm
Alto del producto	43 mm
Largo del product	39.5 mm
Peso del product	0.055 kg

Información de Embalaje

Embalaje Nivel 1 Unidades	box 1 piece
Embalaje Nivel 1 Ancho	46 mm
Embalaje Nivel 1 Alto	46 mm
Embalaje Nivel 1 Largo	46 mm
Embalaje Nivel 1 Peso	0.055 kg

Embalaje Nivel 1 EAN	3471523130173
Package Level 2 Units	box 192 piece
Package Level 2 Gross Weight	10.56 kg
Package Level 3 Units	4608 piece

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85389099
E-Number (Finland)	3706516
E-Number (Sweden)	3211424
Country of Origin	Poland (PL)
Selling Unit of Measure	piece

Certificados y Declaraciones (Número de Documento)

ABS Certificate	ABS_15-GE1349500-PDA_90682247
BV Certificate	BV_2634H24900B0
CB Certificate	CB_SE-93053
CQC Certificate	CQC2011010304496319 CQC2013010304651497
cUL Certificate	UL_20180227_E252354_3_1
Declaration of Conformity - CCC	2020980304001258 2020980304001259
Declaración de conformidad - CE	1SBD250007U1000
DNV Certificate	DNV-GL_TAE00001BV-3
DNV GL Certificate	DNV-GL_TAE00001BV-3
EAC Certificate	EAC_RU C-FR ME77 B03391
Environmental Information	1SBD250143E1000
GL Certificate	DNV-GL_TAE00001BV-3
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
Instrucciones y manuales	1SBC101041M6801
LR Certificate	LR_1300087E1
RINA Certificate	RINA_ELE084013XG
RMRS Certificate	RMRS_1802703280
RoHS Information	1SBD250007U1000
UL Certificate	UL_20091128-E252354-3-1
UL Listing Card	UL_E252354

Descargas Populares

Instrucciones y manuales	1SBC101041M6801
UL Listing Card	UL_E252354

Clasificaciones

ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8538 90 99
UNSPSC	39121500
eClass	V11.0 : 27371302
Object Classification Code	K

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Block Contactors Accessories



storel®
tech
Electricidad Industrial & Doméstica