332-C6



General Information

Extended Product Type: 332-C6

Product ID: 2CMA193529R1000 EAN: 7392696935296

Catalog Description: Connector, 6h, 32A, IP44, 3P+E

Connector, earthing sleeve position 6h, rated current 32A, IP44 splashproof, 3-Long Description:

poles+earth, 50 - 60 Hertz, color code red

Categories

Products » Low Voltage Products and Systems » Industrial Plugs and Sockets » Plugs & Sockets » Connectors

Ordering

EAN: 7392696935296

Minimum Order Quantity: 10 piece

Country of Origin: Czech Republic (CZ)

Dimensions

Product Net Width: 96 mm **Product Net Height:** 96 mm **Product Net Length:** 177 mm **Product Net Depth:** 96 mm

Product Net Weight: 0.273 kg

Container Information

Package Level 1 Width: 180 mm Package Level 1 Length: 155 mm Package Level 1 Height: 378 mm Package Level 1 Gross Weight: 0.273 kg

7392696935296 Package Level 1 EAN:

Package Level 1 Units: 10 piece

Environmental

RoHS Status: Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after

2006-03-01

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 2CMC700005D0001 **Environmental Information:** 2CMC700001D0002

RoHS Information: 2CMC700022

Additional Information

Color:

Additional Information: Cable entry, compression gland

Cable Cross-Section: 2.5 ... 6 mm²

Red Degree of Protection: **IP44**

Polyamide dustrial & Doméstica Enclosure Material:

50 Hz Frequency (f): 60 Hz

Function: Connector

IIT Publishing Status: Level 0 - Information enabled

Invoice Description: Ind. P&S#332-C6

Number of Polesisite uses cookies. By staying here you are agreeing to our use of cookies. Learn more I agree

Object Classification Code: 2CMT005069 Product Main Type: C

Product Name: Industrial Connector

Protection Type: Splashproof

Rated Current (I_n): 32 A

Rated Voltage (U_r): $380 \dots 415 \text{ V}$ RoHS Date: 2009-1

Standards: IEC 60309-1,-2
Suitable For: Connectors

Suitable for Product Class: Industrial Plugs and Sockets

Classifications

E-nummer: 2416186 **UNSPSC:** 39120000





ABB's website uses cookies. By staying here you are agreeing to our use of cookies.

Learn more

I agree