



JA25G

| | | |
|---------------------------------------|--------------------|---|
| Operational Frequency | | 50 - 60Hz |
| Product | | Thermic Relay |
| Current | Ie | 25A |
| Thermic Current | | 1,20-1,75A |
| Calibration Interval | | |
| Usage Category | | AC 3 |
| Mechanical Life | Min Qty | 100000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 600 Elec. 600 |
| Insulation Voltage | Ui | 690V AC |
| Impulse Withstand Voltage | Uimp | 6 kV |
| Dielectric Strength (Body-Contact) | | 1890V AC |
| Dielectric Strength (Contact-Contact) | | 1890V AC |
| Isolation Resistance | | 10 MΩ (500 V DC) |
| Operating Temperature | | -5 / +40 °C |
| Pollution Degree | | 3 |
| Protection Degree | | IP20 |
| Contact Material | | AgNi |
| Cable Section | | 1,5 -2,5mm ² |
| Screw Torque | | 1,8Nm |
| Short Circuit Breaking Capacity | Ics | 50 kA |
| Serial | | JA Series |
| Specifications | | With single phase and three phase protection against overload |
| | | Protection against phase failure |
| | | Manual or automatic reset |
| Standards / Certificates | | TS EN 60947-4-1 |

