

PRODUCT-DETAILS

SH201-C63

Interruptor automático - SH200 - 1P - C - 63 A



Información General

Tipo de producto extendido	SH201-C63
Código de producto	2CDS211001R0634
EAN	4016779699006
Descripción corta	Interruptor automático - SH200 - 1P - C - 63 A
Descripción larga	SH201-C63 MiniCircuitBreaker

Technical

Standards	IEC/EN 60898-1
Product Name	Interruptor automático
Tripping Characteristic	C
Rated Operational Voltage	acc. to IEC 60898-1 230 / 400 V AC
Operational Voltage	Maximum (Incl. Tolerance) 253 V AC Minimum 12 V AC
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Dielectric Test Voltage	50/60 Hz, 1 min: 2 kV
Input Voltage Type	AC
Rated Current (I _n)	63 A
Rated Short-Circuit Capacity (I _{cn})	(230 / 400 V AC) 6 kA

Rated Conditional Short-Circuit Current (I_{nc})	(230 V) 6 kA (400 V) 6 kA
Rated Frequency (f)	50 / 60 Hz
Power Loss	4.8 W at Rated Operating Conditions per Pole 4.8 W
Power Supply Connection	Arbitrary
Contact Position Indication	ON / OFF
Energy Limiting Class	3
Electrical Endurance	10000 AC cycle 20000 cycle
Number of Poles	1
Number of Protected Poles	1
Overvoltage Category	III
Tightening Torque	2 N·m
Actuator Type	Toggle
Screw Terminal Type	Cage Terminal
Actuator Marking	I / O
Actuator Material	Insulation Group II, Black, Sealable
Housing Material	Insulation Group II, RAL 7035
Mounting on DIN Rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Mounting Position	Any
Recommended Screw Driver	Pozidriv 2
Accessories Available	No
Connecting Capacity	Conductor 25 / 25 mm ² Flexible with Ferrule 0.75 ... 16 mm ² Flexible 0.75 ... 16 mm ² Rigid 0.75 ... 25 mm ² Stranded 0.75 ... 25 mm ²
Installation Size	acc. to DIN 43880 1
Terminal Type	Screw Terminals

Ambiente

Temperatura ambiente	Funcionamiento -25 ... +55 °C Almacenamiento -40 ... +70 °C
Reference Ambient Air Temperature	30 °C
Grado de protección	IP20 Enclosure with Cover IP40
Pollution Degree	2
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations acc. to IEC 60068-2-6	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
Resistance to Shock acc. to IEC 60068-2-27	25g / 2 shocks / 13 ms
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	2CDK400030D0201

Dimensiones

Width in Number of Modular Spacings	1
Ancho del product	17.5 mm

Alto del producto	85 mm
Largo del product	69 mm
Peso del product	0.125 kg
Pole Net Weight	0.115 kg
Built-In Depth (t ₂)	69 mm

Información de Embalaje

Embalaje Nivel 1 Unidades	carton 10 piece
Embalaje Nivel 1 Ancho	80 mm
Embalaje Nivel 1 Alto	92 mm
Embalaje Nivel 1 Largo	183 mm
Embalaje Nivel 1 Peso	1.3 kg
Package Level 2 Units	120 piece
Package Level 2 EAN	4016779991179

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85362010
Country of Origin	Germany (DE)
Selling Unit of Measure	piece

Certificados y Declaraciones (Número de Documento)

Certification Agency	EN IEC
Declaración de conformidad - CE	9AKK107046A5460
Environmental Information	2CDK400030D0201
Instrucciones y manuales	Printed on packaging
RoHS Information	2CDK400030D0201

Descargas Populares

Ficha técnica, información técnica	2CSC400030D0202
Instrucciones y manuales	Printed on packaging

Clasificaciones

ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
EPLAN Catalog Tree	Electrical engineering / Protection devices / General
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 20 10
UNSPSC	39121614
eClass	V11.0 : 27141901
Object Classification Code	F

Categorías

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Interruptores automáticos modulares

