

PRODUCT-DETAILS

332EP6

Industrial Plugs, 3P+E, 32A, 380 ... 415 V



Información General

| | |
|----------------------------|--|
| Tipo de producto extendido | 332EP6 |
| Código de producto | 2CMA101984R1000 |
| EAN | 7392696019842 |
| Descripción corta | Industrial Plugs, 3P+E, 32A, 380 ... 415 V |
| Descripción larga | Industrial Plugs, 3P+E, 32A, 380 ... 415 V Clock Position Of Grounding Contact 6 hour Color code Red |

Clasificación

| | |
|---------------------------|---------------------|
| E-Number (Sweden) | E2416174 |
| E-Number (Finland) | 2420079 |
| E-Number (Norway) | 1540714 |
| EAN | 7392696019842 |
| Country of Origin | Czech Republic (CZ) |
| Cantidad mínima de pedido | 10 piece |

Dimensiones

| | |
|-------------------|---------|
| Ancho del product | 79 mm |
| Alto del producto | 83 mm |
| Peso del product | 0.23 kg |

Información de Embalaje

| | |
|--------------------------------|-------------------------|
| Embalaje Nivel 1 Ancho | 154 mm |
| Embalaje Nivel 1 Largo | 182 mm |
| Embalaje Nivel 1 Alto | 378 mm |
| Embalaje Nivel 1 Peso | 2.3 kg |
| Embalaje Nivel 1 EAN | 7392696030168 |
| Embalaje Nivel 1 Unidades | box 10 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 1055 kg |
| Package Level 2 EAN | 7392696066617 |
| Package Level 2 Units | pallet (lift) 450 piece |

Ambiente

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificados y Declaraciones (Número de Documento)

| | |
|---------------------------------|-----------------|
| CB Certificate | 2CHC660167X0201 |
| Declaración de conformidad - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1617364 |
| REACH Declaration | 2CMC700005D0001 |

Información Adicional

| | |
|---------------------------------|---------------------------|
| Additional Information | 3P+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 2.5 ... 6 mm ² |
| Cable Diameter | 22 mm |
| Cable Entry Position | Swivel |
| Color | Red |
| Connection Type | Screw |
| Grado de protección | IP44 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Plug |
| Housing Material | Plastic (PA) |
| Invoice Description | Ind. P&S#332EP6 |
| Number of Poles | 4 |
| Order Multiple | 10 piece |
| Product Main Type | EP |
| Product Name | Industrial Plug |
| Protection Type | Splashproof |
| Rated Current (I _n) | 32 A |

| | |
|----------------------------|----------------------------------|
| Rated Voltage (U_r) | 380 ... 415 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2 |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instrucciones y manuales | 2CMC700014C0016 |
| RAL Number | RAL 7012 - Gris basalto |

Clasificaciones

| | |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 12 ... 10 AWG |
| Tightening Torque | WireClamp1.2 N·m |

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Plugs

