

PRODUCT-DETAILS

332P6W

Ind. P&S#332P6W



Información General

Tipo de producto extendido	332P6W
Código de producto	2CMA166738R1000
EAN	7392696667388
Descripción corta	Ind. P&S#332P6W
Descripción larga	Plug, earthing sleeve position 6h, rated current 32A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2416268
E-Number (Finland)	2421644
E-Number (Norway)	2416268
EAN	7392696667388
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	1 piece

Dimensiones

Ancho del product	94 mm
Alto del producto	94 mm
Peso del product	0.3 kg

Información de Embalaje

Embalaje Nivel 1 Ancho	95 mm
Embalaje Nivel 1 Largo	95 mm
Embalaje Nivel 1 Alto	175 mm
Embalaje Nivel 1 Peso	0.4 kg
Embalaje Nivel 1 EAN	7392696667388
Embalaje Nivel 1 Unidades	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	180 kg
Package Level 2 EAN	7392696070065
Package Level 2 Units	pallet (lift) 400 piece

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm ²
Cable Diameter	13 ... 21.5 mm
Cable Entry Position	Cable entry compression gland
Color	Red
Connection Type	Screw
Grado de protección	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#332P6W
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TP
Product Name	Industrial Plug
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Voltage (U _r)	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2

Suitable For	Plugs
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
RAL Number	RAL 7001 - Gris plata

Clasificaciones

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Plugs



storel®
 tech
 Electricidad Industrial & Doméstica