


PRODUCT-DETAILS

# 363P6W

Ind. P&S#363P6W



## Información General

Tipo de producto extendido	363P6W
Código de producto	2CMA166786R1000
EAN	7392696667869
Descripción corta	Ind. P&S#363P6W
Descripción larga	Plug, earthing sleeve position 6h, rated current 63A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red

## Clasificación

E-Number (Sweden)	E2416288
E-Number (Finland)	2421648
E-Number (Norway)	1563673
EAN	7392696667869
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	1 piece

## Dimensiones

Ancho del product	114 mm
Alto del producto	114 mm
Peso del product	1.05 kg
Mechanical Drawings	9AKK107492A4181

## Información de Embalaje

Embalaje Nivel 1 Ancho	120 mm
Embalaje Nivel 1 Largo	138 mm
Embalaje Nivel 1 Alto	285 mm
Embalaje Nivel 1 Peso	1.14 kg
Embalaje Nivel 1 EAN	7392696667869
Embalaje Nivel 1 Unidades	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	156.8 kg
Package Level 2 EAN	7392696070133
Package Level 2 Units	pallet (lift) 120 piece

## Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

## Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	4 ... 16 mm <sup>2</sup>
Cable Diameter	17 ... 35 mm
Cable Entry Position	Cable entry, compression gland, internal and external cable clamp
Color	Red
Connection Type	Screw
Grado de protección	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#363P6W
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TP
Product Name	Industrial Plug
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	63 A
Rated Voltage (U <sub>r</sub> )	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2

Suitable For	Plugs
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7001 - Gris plata

## Clasificaciones



eClass	27440509
UNSPSC	39120000

## Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Plugs



storel®  
 JTECH  
 Electricidad Industrial & Doméstica