

PRODUCT-DETAILS

316RAM9

Socket-outlet, panel mounting, 9h, 16A, IP44, minimized flange, angled, 3P+E



Información General

Tipo de producto extendido	316RAM9
Código de producto	2CMA170014R1000
EAN	7392696700146
Descripción corta	Socket-outlet, panel mounting, 9h, 16A, IP44, minimized flange, angled, 3P+E
Descripción larga	Panel mounted socket, earthing sleeve position 9h, rated current 16A, IP44 splashproof, minimized flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Blue

Clasificación

E-Number (Sweden)	2416470
E-Number (Finland)	2416470
E-Number (Norway)	2416470
EAN	7392696700146
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	10 piece

Dimensiones

Ancho del product	83 mm
Alto del producto	89 mm
Peso del product	0.24 kg

Información de Embalaje

Embalaje Nivel 1 Ancho	154 mm
Embalaje Nivel 1 Largo	182 mm
Embalaje Nivel 1 Alto	378 mm
Embalaje Nivel 1 Peso	2.4 kg
Embalaje Nivel 1 EAN	7392696702126
Embalaje Nivel 1 Unidades	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1100 kg
Package Level 2 EAN	7392696077798
Package Level 2 Units	pallet (lift) 450 piece

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificados y Declaraciones (Número de Documento)

CB Certificate	2CHC660153X0201
Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614201
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	13 ... 17 mm
Color	Blue
Connection Type	Screw
Grado de protección	IP44
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316RAM9
Mounting Holes	66x66
Mounting Type	Minimized angled flange
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ERAM
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Frequency (f)	50...60 Hz

Rated Voltage (U _r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
RAL Number	RAL 7001 - Gris plata

Clasificaciones

eClass	27440504
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Socket Outlets for Panel Mounting

